



### Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Rotary head
Product compatibility	XCKJ
Associated lever	ZCKY43 ZCKY41 ZCKY51 ZCKY52 ZCKY11 ZCKY91 ZCKY13 ZCKY59 ZCKY81 ZCKY14 ZCKY53
Associated body	ZCKJ5H29 ZCKJ4 ZCKJD39H7 ZCKJ7H7 ZCKJ4H7 ZCKJ404 ZCKJD31H7 ZCKJD39 ZCKJ21 ZCKJ21H29 ZCKJ1H7 ZCKJD35H29 ZCKJD37H7 ZCKJD39H29 ZCKJ9H29 ZCKJ5H7 ZCKJ6

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ41H7  
 ZCKJD37  
 ZCKJ6H29  
 ZCKJ9H7  
 ZCKJ6H7  
 ZCKJD31  
 ZCKJD31H29  
 ZCKJ7H29  
 ZCKJ8  
 ZCKJ2H7  
 ZCKJ2H29  
 ZCKJ5  
 ZCKJ2  
 ZCKJ404H29  
 ZCKJD37H29  
 ZCKJ4104  
 ZCKJ404H7  
 ZCKJ21H7  
 ZCKJ11  
 ZCKJD35  
 ZCKJD35H7  
 ZCKJ11H7  
 ZCKJ1  
 ZCKJ4104H7  
 ZCKJ8H29  
 ZCKJ11H29  
 ZCKJ41H29  
 ZCKJ4H29  
 ZCKJ4104H29  
 ZCKJ8H7  
 ZCKJ9  
 ZCKJ7  
 ZCKJ41  
 ZCKJ1H29

Movement of operating head	Rotary
Type of operator	Without operating lever spring return
Type of approach	Lateral approach 1 or 2 programmable direction

### Complementary

Switch actuation	CW and/or CCW From left and/or right
Positive opening	With
Head material	Metal

### Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

### Ordering and shipping details

Category	22411 - LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	T
GTIN	00785901256373
Nbr. of units in pkg.	1
Package weight(Lbs)	0.02
Returnability	Y
Country of origin	ID

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0851 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations
<b>Contractual warranty</b>	
Warranty period	18 months