



Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|----------------------------|--------------------------------------|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch lever |
| Device short name | ZCKY |
| Product compatibility | XCKJ |
| Associated head | ZCKE05 |
| Movement of operating head | Rotary |
| Type of operator | Roller lever spring return metal (-) |
| Type of approach | Lateral approach |

Complementary

| | |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | 50...248 °F (10...120 °C) high temperature -40...158 °F (-40...70 °C) low temperature -13...158 °F (-25...70 °C) standard environment |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) low temperature 50...248 °F (10...120 °C) high temperature -40...158 °F (-40...70 °C) standard environment |
| Environmental characteristic | Low temperature Standard environment High temperature |

Ordering and shipping details

| | |
|----------|---------------------------------|
| Category | 22411 - LIMIT SWITCHES,IEC,XCKJ |
|----------|---------------------------------|

| | |
|-----------------------|----------------------|
| Discount Schedule | T |
| GTIN | 00785901646303 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 5.999999999999998E-2 |
| Returnability | Y |
| Country of origin | ID |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0851 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|