




NEMA Non-Combination Contactors/Starters and Combination Contactors/Starters

Circuit Breaker Accessories

For use on Bulletins 503, 503L, 507, 507X, 513, 513H, 513M, 513V, 523, 533, 543, 573, 1243, 1273, 1283, 1233X, and 1233V

	Description	NEMA Size	Cat. No.	
	Circuit Breaker Kits			
	3 A, 0...1/3 Hp @ 200 and 230V 3 A, 0...1 Hp @ 460 and 575V	0...1	1401-N60	
	7 A, 0.5...1 Hp @ 200 and 230V 7 A, 1.5...3 Hp @ 460 and 575V	0...1	1401-N61	
	15 A, 1.5...3 Hp @ 200 and 230V 15 A, 5...7.5 Hp @ 460 and 575V	0...1	1401-N62	
	30 A, 5 Hp @ 200V 30 A, 5...7.5 Hp @ 230V 30 A, 10...15 Hp @ 460 and 575V	1...2	1401-N63	
	50 A, 5...10 Hp @ 200V 50 A, 10 Hp @ 230V 50 A, 20...25 Hp @ 460V 50 A, 20...30 Hp @ 575V	1...3	1401-N64	
	100 A, 15...25 Hp @ 200 and 230V 100 A, 30...50 Hp @ 460V 100 A, 40...50 Hp @ 575V	2...4	1401-N65	
	150 A, 30 Hp @ 200V 150 A, 30...40 Hp @ 230V 150 A, 60...75 Hp @ 460V 150 A, 75...100 Hp @ 575 V	3...4	1401-N66	
	250 A, 125 Hp @ 575V	5	1401-N68	
	250 A, 50...60 Hp @ 200V 250 A, 60...75 Hp @ 230V		1401-N69	
		Auxiliary Contacts for Disconnect Switches		
		One normally open (1 N.O.) Adapter kit may be required. * Bolted — One normally open (1 N.O.)* Unilock — One normally open (1 N.O.)*	0...5‡ 4...5§	1495-N8
One normally closed (1 N.C.) Adapter kit may be required.* Bolted — One normally closed (1 N.C.)* Unilock — One normally closed (1 N.C.)*	0...5	1495-N9		
	Unilock — One normally open (1 N.O.)*	0...2	1495-N14	
	Unilock — One normally closed (1 N.C.)*	0...2	1495-N15	
	HMCP Circuit Breaker Adapter Kits (for mounting 1 or 2 auxiliary contacts)	5	1495-N16	
	400 A Frame*			
	150 A Frame	3...4	1495-N21	
	250 A Frame - Enclosure Type 1, 3R/4/12, 3R and 4/4X (stainless steel)	4...5♣	1495-N22	
	250 A Frame - Enclosure Type 7 & 9 (bolted & Unilock) and 4/4X (non-metallic)	0...5➤		
	250 A Frame - Enclosure Type 1, 3R/4/12, 3R, and 4/4X (stainless steel)	4	1495-N23	
Unilock — 150 A Frame*	3...4	1495-N21		
Unilock — 250 A Frame*	4...5	1495-N22		

* Contact Ratings — NEMA B600 and NEMA P600.

* Not available on larger sizes 6...9.

‡ For Bolted and 1 N.O.

§ For Unilock 1 N.C.

♣ For Enclosure Type 1.










➤ For Enclosure Types 7 & 9.

1

NEMA Disconnect Switches

Accessories

1

		Description	For Use With	Cat. No.
	Auxiliary Contacts	1 N.O. Contact	1494C, 1494F, 1494V, and 1494G (30...400 A) Disconnect Switches	1495-N8
		1 N.O. Contact (low-level switching)		1495-N8X
		1 N.C. Contact	1494D, 1494V* (125...400 A Frame) Circuit Breakers	1495-N9
		1 N.C. Contact (low-level switching)		1495-N9X
  <p><i>Cat. No. 595-A</i> <i>Cat. No. 595-B</i></p>	Auxiliary Contacts (600 A Disconnect Switch only)	1 N.O. Contact	1494C, 1494G, and 1494V Disconnect Switches 600 A only	595-A
	1 N.C. Contact	595-B		
 <p><i>Cat. No. 595-N1</i></p>	Auxiliary Contact Adapter Kit For Disconnect Switches	600 A		* 595-N1
 <p><i>Cat. No. 1495-N24</i></p>	Auxiliary Contact Adapter Kit For Disconnect Switches with Left-Hand Mechanism	30...100 A Disconnect Switch	1494V Disconnect Switch with Left-Hand Mechanism, 30...100 A	* 1495-N24
		200...400 A Disconnect Switch	1494V Disconnect Switch with Left-Hand Mechanism, 200...400 A	* 1495-N25
  <p><i>Cat. No. 1495-N21</i> <i>Cat. No. 1495-N23</i></p>	Auxiliary Contact Adapter Kit For Circuit Breakers	125 A and 150 A Frame Allen-Bradley, Cutler-Hammer	1494D, 1494V Circuit Breakers	* 1495-N21
		250 A, 400 A Frame Allen-Bradley, Cutler-Hammer	1494V Circuit Breaker	* 1495-N23
		250 A Frame Allen-Bradley, Cutler-Hammer	1494D Circuit Breaker	* 1495-N22
		400 A Frame Allen-Bradley, Cutler-Hammer	1494D Circuit Breaker	* 1495-N16
		600 A, 800 A, 1200 A Frame Cutler-Hammer	1494D Circuit Breaker	* 1495-N13
 <p><i>Cat. No. 1495-N34</i></p>	Electrical Interlocks	1 N.O. and 1 N.C. — early make/break	1494C, 1494G & 1494V Disconnect Switches with Left-/Right-Hand Mechanism, 30...100 A & Right-Hand Mechanism, 600 A	† 1495-N34
		2 N.O. and 2 N.C. — early make/break		† 1495-N35
		1 N.O. and 1 N.C. — early make/break	1494C, 1494G, & 1494V Disconnect Switch with Right-Hand Mechanism, 200 A, 400 A	1495-N43
		2 N.O. and 2 N.C. — early make/break		1495-N44
		1 N.O. and 1 N.C. — early make/break	1494C and 1494V Disconnect Switch with Left-Hand Mechanism, 30...100 A	1495-N37
		2 N.O. and 2 N.C. — early make/break		1495-N38
		 <p><i>Cat. No. 1495-N35</i></p>	Electrical Interlocks	1 N.O. and 1 N.C. — early make/break
2 N.O. and 2 N.C. — early make/break	1495-N40			
1 N.O. and 1 N.C. — early make/break	1494V Disconnect Switch with Left-Hand Mechanism, 400 A			1495-N41
2 N.O. and 2 N.C. — early make/break				1495-N42
10 A DPDT — early break (for 30 A, Type 1 & 3R only)	1494H Safety Switch			1495-N77
15 A DPDT — early break (for 30 A, Type 12)				1495-N78
	Electrical Interlock Adapter Kit	600 A Disconnect Switch	1494C, 1494G, 1494V Disconnect Switch	1495-N36

* Requires an adapter kit on new installations.

* One adapter kit enables up to two auxiliary contacts to be installed.

† Additional adapter kit (**Cat. No. 1495-N36**) required for installation on 600 A switch.