

MICRO SWITCH™ GK Dual-Entry Safety Switch

Product Nomenclature

Honeywell

For example, a **GKBA1L6** part number would define a GK Series dual-entry, key-operated switch with no indicator, a 0.5 in NPT conduit opening, 1NC/1NO snap-action circuitry, head opening to the front and top, and using a straight key.



GK

B

A

1

Switch Type

Body/
Indicator

Conduit

Circuitry

Head

Key

GK Series
Dual-Entry
Key-Operated
Safety Switch

B No indicator	A 1/2 NPT	1 1NC/1NO snap action	12 2NC/1NO, BBM slow acting	L Opening to front & top	6 Straight
C Single LED indicator	B PG 13.5	2 2NC/2NO snap action	14 2NC/2NO, BBM slow acting	M Opening to right & top	7 90 degree
D Double LED indicator	C 20 mm	3 1NC/1NO, BBM slow acting	16 3NC/1NO, BBM slow acting	N Opening to back & top	8 Up-down, spring loaded
		4 1NC/1NO, MBB slow acting	30 4NC, gold slow acting	P Opening to left & top	9 Side-side, spring loaded
		6 2NC slow acting	32 2NC/1NO, BBM gold, slow acting		X No key
		7 1NC/1NO, gold snap action	34 2NC/2NO, BBM gold, slow acting		
		10 4NC slow acting	36 3NC/1NO, BBM gold, slow acting		

NOTE: not all combinations of model code are available. Please contact your Honeywell provider/representative for assistance.

* A key actuator (ordered separately) is required for each switch.

NOTE: not all combinations of model code are available.
Please contact your Honeywell provider/representative for assistance.

* A key actuator (ordered separately) is required for each switch.

*Keys Listing

GKZ56
GKZ57
GKZ58
GKZ59

Key style

1 - straight
2 - 90°
3 - up/down
4 - side/side