




22.5 mm Push Buttons

IP66, Type 4/4X/13 (Plastic) — IP66, Type 4/13 (Metal)

Accessories, Continued

Locking Attachments and Guards

	Description		Cat. No.	
	Mushroom Locking Attachment Used to lock momentary mushroom push buttons in the depressed position. In the depressed position, N.C. contacts are open, N.O. contacts may or may not be open, N.C.L.B. (late break) contacts may or may not be open, and N.O.E.M. (early break) contacts are closed. This device is used with the following operators: 800E_-M_ 800E_-MT_		800E-AML1	
	800E_-MP2_ 800E_-MMP2_ 800E_-MP3_ 800E_-MMP3_ 800E_-LM_ 800E_-LMP2 800E_-LMP3 800E_-MM_ 800E_-MTS3_ 800E_-MTS4_ 800E_-MTS6		800E-AML2	
	800E_-MJT ❶		800E-AMLJ1	
	800E_-MJ ❶		800E-AMLJ2	
	800E_-MTS6_ 800E_-MJP2_ 800E_-MJP3_ 800E_-LMJ_ 800E_-LMJP2_ 800E_-LMJP3_		800E-AMLJ3	
		Locking Cover Used on flush, extended, and guarded momentary and alternate action operators, standard knob selector switch operators, and potentiometer operators.		800E-AL01
	Description	Type	Cat. No.	
	Plastic Bezel Ring Clear plastic bezel rings are meant as replacements for all 800E round illuminated flush push buttons. Black plastic bezel rings are meant as replacements for 800EP guarded non-illuminated push buttons. Plastic bezel rings are sold in multiples of 10. Order (quantity) 10 to receive one package of 10 pieces.	Clear plastic Black plastic	800E-ALB1 800EP-AG1	

❶ The last position in the catalog string is numeric only (i.e., 1, 2, 3, 4, 5, 6, or 8).