

Electromechanical Burner Controls

ST71 Pre-Purge Timer (for R4795)

Application: Prepurge Timer for R4795 Control Systems.
Application: Prepurge Timer for R4795 Control Systems

Temperature Range:
-20 F to +125 F @ 60 Hz (-20 C to +52 C @ 60 Hz)
-20 F to +115 F @ 50 Hz (-20 C to +46 C @ 50 Hz)

Product Number	Purging Time	Description
ST71A1000	7 sec	Prepurge Timer for R4795 Control Systems
ST71A1018	30 sec	Prepurge Timer for R4795 Control Systems
ST71A1026	60 sec	Prepurge Timer for R4795 Control Systems
ST71A1034	90 sec	Prepurge Timer for R4795 Control Systems
ST71A1042	10 sec	Prepurge Timer for R4795 Control Systems

ST795 Purge Timer (for R7795)

Application: Plug in Purge Timer for use with R7795 Full Function
Primary Safety Control.

Temperature Range:
-40 F to +120 F @ 50 Hz (-40 C to +49 C @ 50 Hz)
-40 F to +135 F @ 60 Hz (-40 C to +57 C @ 60 Hz)

Application: Plug in Purge Timer for use with R7795 Full Function
Primary Safety Control

Product Number	Purging Time	Description
ST795A1007	1.5 sec	Prepurge Timer for R7795 Control Systems
ST795A1015	7 sec	Prepurge Timer for R7795 Control Systems
ST795A1023	10 sec	Prepurge Timer for R7795 Control Systems
ST795A1031	30 sec	Prepurge Timer for R7795 Control Systems
ST795A1049	60 sec	Prepurge Timer for R7795 Control Systems
ST795A1056	90 sec	Prepurge Timer for R7795 Control Systems

Primary Control Accessories

Product Number	Description	Used With
118702E	Remote Reset Cover for RA890F, G and R4795, 120V, 50-60 Hz	—
202980	Flame Relay for FSP5075A1	FSP5075A1
202981	Load Relay for FSP5075A1	FSP5075A1
203056	Flame Relay for FSP5075A3	FSP5075A3